

### DIGITAL PODIUM SPECIFICATIONS OPTION-1 for Big Class Room

ITEM	SPECIFICATION	
<b>Enclosure</b>	<ol style="list-style-type: none"> <li>1. Free Standing Wheel Mounted, 2 Wheels Free &amp; 2Wheels lockable</li> <li>2. Screw less chassis made of 1.6mm thick MS / CRCA sheet with polymer powder coated.</li> <li>3. Lockable tray for Document, Visualizer / Document Camera &amp; Key Board.</li> <li>4. Display tilting facility by electrical switch.</li> <li>5. Space / Acrylic sheet for Customer Logo.</li> <li>6. <b>Port / Connectors</b> –               <ol style="list-style-type: none"> <li>1. Socket for Gooseneck Mic</li> <li>2. 3Pin Power Socket,</li> <li>3. Audio IN,</li> <li>4. 2xVGA IN,</li> <li>5. RJ45 LAN,</li> <li>6. 2xUSB,</li> <li>7. VGA out-Projector,</li> <li>8. Audio out - Speakers,</li> </ol> </li> </ol>	
<b>DISPLAY</b>	<p><b>21.5" Wide Active Matrix Colored</b> Interactive Dual Touch (Pen &amp; Finger touch) Penal Display with Auto Display tilting facility by electrical switch.</p> <ul style="list-style-type: none"> <li>• Display Size &amp; Type : 21.5" Active Matrix TFT LCD</li> <li>• Aspect Ratio : 16:9/16:10</li> <li>• Native Resolution: 1920 x 1080 @ 60 Hz</li> <li>• Pixel Response Time : 16ms</li> <li>• Color : 16.7 Million</li> <li>• Brightness (Typ.) LCD Panel: 250 cd/m<sup>2</sup></li> <li>• Viewing Angle : 178° x 178°</li> <li>• Input Video Signal Connector: VGA / DVI-D/HDMI</li> <li>• Touch Technology : Projected Capacitive Touch (P-Cap)</li> <li>• Input Method : Finger / Stylus</li> <li>• Touch Point : 10 Touch</li> <li>• Touch Interface : USB</li> </ul>	
<b>CPU</b>	<p><b>SYSTEM Details</b></p> <ul style="list-style-type: none"> <li>• <b>Intel Core i3 2.0 Processor</b> or higher processor</li> <li>• <b>Suitable</b> Express Chipset,</li> <li>• <b>8GB</b> RAM,</li> <li>• <b>500GB</b> HDD,</li> <li>• <b>OS</b> : Windows 10 Prof.</li> </ul>	
<b>Audio System</b>	<ul style="list-style-type: none"> <li>• <b>60 Watt Audio Amplifier</b> with           <ol style="list-style-type: none"> <li>i. 3Mic &amp; 1Aux Input</li> <li>ii. 60Watt RMS at 5% THD,</li> <li>iii. Freq. Response : 50-15000Hz <math>\pm</math>3dB</li> <li>iv. Signal to noise Ratio : 60dB</li> <li>v. Speaker Output – 4, 8, 16 Ohm&amp;100V</li> </ol> </li> <li>• <b>Speakers</b> <ol style="list-style-type: none"> <li>i. 4x15 Watt wall Mount Speakers</li> <li>ii. Freq. Response : 150-10000Hz</li> </ol> </li> </ul>	

	<ul style="list-style-type: none"> <li>• <b>Gooseneck Mic -1No.</b> <ul style="list-style-type: none"> <li>i. Length : 460mm (18")</li> <li>ii. Freq. Response : 50-16000Hz</li> <li>iii. Impedance : 1000Ohm</li> </ul> </li> <li>• 1xHandheld wireless Mic.</li> <li>• 1x wireless Collar Mic.</li> </ul>	
<b>AV Controller</b>	<ul style="list-style-type: none"> <li>• Digital Control panel with HDMI interface for External Device connectivity / switching options with of different devices.           <ul style="list-style-type: none"> <li>i. 3 Inputs – PC, Laptop &amp; Visualizer</li> <li>ii. 2 output – Display &amp; Projector</li> </ul> </li> </ul>	

### OPTION-2 for Small Class Room

ITEM	SPECIFICATION	
<b>Enclosure</b>	<ol style="list-style-type: none"> <li>1. Free Standing Wheel Mounted, 2 Wheels Free &amp; 2Wheels lockable</li> <li>2. Screw less chassis made of 1.6mm thick MS / CRCA sheet with polymer powder coated.</li> <li>3. Space / Acrylic sheet for Customer Logo.</li> <li>4. <b>Port / Connectors</b> –           <ul style="list-style-type: none"> <li>• Socket for Gooseneck Mic</li> <li>• 3Pin Power Socket,</li> <li>• Audio IN,</li> <li>• 1xVGA IN,</li> <li>• RJ45 LAN,</li> <li>• VGA out-Projector,</li> <li>• Audio out - Speakers,</li> </ul> </li> </ol>	
<b>Audio System</b>	<ul style="list-style-type: none"> <li>• <b>60 Watt Audio Amplifier</b> with           <ol style="list-style-type: none"> <li>i. 4Mic &amp; 1Aux Input</li> <li>ii. 60Watt RMS at 5% THD,</li> <li>iii. Freq. Response : 50-15000Hz <math>\pm</math>3dB</li> <li>iv. Signal to noise Ratio : 60dB</li> <li>v. Speaker Output – 4, 8, 16 Ohm&amp;100V</li> </ol> </li> <li>• <b>Speakers</b> <ol style="list-style-type: none"> <li>i. 2x15 Watt wall Mount Speakers</li> <li>ii. Freq. Response : 150-10000Hz</li> </ol> </li> <li>• <b>Gooseneck Mic -1Nos..</b> <ol style="list-style-type: none"> <li>i. Length : 22 Inches</li> <li>ii. Freq. Response : 50-16000Hz</li> <li>iii. Impedance : 1000Ohm</li> </ol> </li> <li>• 1xHandheld wireless Mic.</li> <li>• 1x wireless Collar Mic.</li> </ul>	

For Agmatel India Pvt. Ltd.