



## **2-Channel Rework Station Set, 200 W (300 W)**

Item No: T0053380699N

2-Channel Rework Station Set, 200 W (300 W)

### **KEY FEATURES**

- + Power unit WR 2, 2 channels with soldering iron WP 80, desoldering iron DSX 80
- + Small repair set for all rework applications
- + Simultaneous operation of up to 2 soldering tools (hot air and desoldering iron at the same time is not possible)

## TECHNICAL DATA

Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm Jack Bush (Initial State-Hard-Grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001D
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Maximum Volume	0.7 bar
Number of Channels	2
Overcurrent Release	1,6 A
Power	250 W (300 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±17 °F
Temperature Accuracy for Hot Air	±30 °C
Temperature Range °C	50 - 550 °C
Temperature Range °F	150 - 950 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
UPC	037103305527
Voltage	230 V